

# MESH REINFORCEMENT TO B.S. 4483



	British Standard Reference	Wire Spacing		Wire Diameter		Cross Sectional Area per Metre Width		Nominal Mass kg/m <sup>2</sup>
		Longitudinal mm	Cross mm	Longitudinal mm	Cross mm	Longitudinal mm <sup>2</sup>	Cross mm <sup>2</sup>	
<b>Square Mesh Fabric</b>	A 565	200	200	12	12	565	565	8.88
	A 393	200	200	10	10	393	393	6.16
	A 252	200	200	8	8	252	252	3.95
	A 193	200	200	7	7	193	193	3.02
	A 142	200	200	6	6	142	142	2.22
	A 98	200	200	5	5	98	98	1.54
<b>Structural Fabric</b>	B 1131	100	200	12	8	1131	252	10.90
	B 785	100	200	10	8	785	252	8.14
	B 503	100	200	8	8	503	252	5.93
	B 385	100	200	7	7	385	193	4.53
	B 283	100	200	6	7	283	193	3.73
	B 196	100	200	5	7	196	193	3.05
<b>Long Mesh Fabric</b>	C 785	100	400	10	6	785	70.8	6.72
	C 636	100	400	9	6	636	70.8	5.55
	C 503	100	400	8	5	503	49.0	4.34
	C 385	100	400	7	5	385	49.0	3.41
	C 283	100	400	6	5	283	49.0	2.61
<b>Wrapping Fabric</b>	D 49	100	100	2.5	2.5	49.1	49.1	0.77
<b>Additional Range</b>	Equiv. A 63	150	150	6.34	6.34	210	210	3.31
	Equiv. A 65	150	150	5.34	5.34	149	149	2.34
		150	150	5	5	131	131	2.06
		100	100	5	5	196	196	3.08

## SHEET TYPES

- STANDARD STOCK SHEETS** – 4.8 M x 2.4 M
- SPECIAL SHEETS** – Up to 12 M x 3 M
- ENGINEERED SHEETS** – Diameter, spacing and sheet size to specific requirements.